

Back Boxes



Standard of Compliance BS EN60670 BS 4662

Metal Switch & Socket Boxes

List No.	Description	Pack Qty		
Standard Pattern				
EPD	16mm 1 gang fitted with 1 adj & 1 fixed lug	20		
E11	25mm1 gang fitted with1 adj & 3 fixed lugs	100		
E12	25mm 2 gang fitted with 1 adj & 1 fixed lug	50		
ES1	35mm 1 gang fitted with 1 adj & 3 fixed lugs	100		
ES2	35mm 2 gang fitted with 1 adj & 1 fixed lug	50		
AR1	27mm 1 gang architrave fitted with 2 fixed lugs	20		
CB2	47mm 1 gang fitted with 1 adj & 3 fixed lugs	10		
SB1	47mm 2 gang fitted with 1 adj & 1 fixed lug	5		
Dual Pattern				
DES1	25mm 2 x 1 gang each outlet fitted with 1 adj & 8 fixed lugs	5		
DES2	35mm 2 x 1 gang each outlet fitted with 1 adj & 4 fixed lugs	5		
DES2/1	35mm 2 + 1 gang each outlet fitted with 1 adj & 4 fixed lugs	5		
DES2/3	35mm 3 x 1 gang	5		
DES211	35mm 2 x 1 x 1 gang	5		
DES22	35mm 2 x 2 gang	5		
DES221	35mm 2 x 2 x 1 gang	5		
Extension Pattern				
EPDEB	16mm 1 gang fitted with 1 adj & 1 fixed lug	20		
E11EB	25mm 1 gang fitted with 1 adj & 3 fixed lugs	10		
E12EB	25mm 2 gang fitted with 1 adj & 1 fixed lug	10		
ES1EB	35mm 1 gang fitted with 1 adj & 3 fixed lugs	10		
ES2EB	35mm 2 gang fitted with 1 adj & 1 fixed lug	10		



Insulated Connector Boxes





Standard of Compliance

IEC 60998

Certified

- Specifications
- IP55
- Snap-fit cover
- Flame retardant
- Halogen free *IP54 5 way terminal provided

IP55 Moulded Connector Boxes

List No.	Size	Fairlead Entries	Pack Qty
FD7	77 x 75 x 42mm	7 x 19mm	10
FD10	93 x 43 x 42mm	6 x 19 + 4 x 15mm	10
FD12	93 x 90 x 48mm	12 x 19mm	10
8205*	75 x 75 x 37mm	7 x 19mm	10

Gel



Specifications

- Offers IP68 protection
- Re-enterable & reusable
- No Shelf life limitation
- Removable
- Dielectric strength > 22Kv
- Installations up to 1Kv & 140°C
- Non-toxic

Note

 $\bullet \ \hbox{Connection box, wires}$ & glands not included

IP68 Insulating & Sealing Gel

List No.	Description	Pack Qty
BG170	170ml mix-sachet	1
BG250	250ml mix-sachet	1
BG400	400ml mix-sachet	1

Compound



Specifications

- None Flammable (at normal temperatures)
- Water resistant mastic
- None-hazardous
- · Remains plastic malleable (none hardening)
- Provides moisture or fume barrier
- · Ideal for bulkhead sealing

Plastic Sealing Compound

List No.	Description	Pack Qty
N653/03	1kg tub - green	1