

450V In-line Cable Connectors - IP68 Waterproof



Standard of Compliance
IEC60998-2-1:2004
IEC62444:2013
IEC60529:1991+A1:2000
+A2:2013

Specifications
• IP68 (3 bar)

3 Pole Straight

List No.	Terminal	Amps Max	Cable O/D Min-Max	Pack Qty
JOW3	3 pole straight	16A	5 - 10mm	1



Standard of Compliance
IEC60998-2-1:2004
IEC62444:2013
IEC60529:1991+A1:2000
+A2:2013

Specifications
• IP68 (3 bar)

4 Pole Fast Fit

List No.	Terminal	Amps Max	Cable O/D Min-Max	Pack Qty
JOW4PIN	4 pole pin & socket, fast fit	16A	5 - 10mm	1



Standard of Compliance
IEC60998-2-1:2004
IEC62444:2013
IEC60529:1991+A1:2000
+A2:2013

Specifications
• IP68 (3 bar)

3 Pole 'T'

List No.	Terminal	Amps Max	Cable O/D Min-Max	Pack Qty
JOW3T	3 pole 'T'	24A	5 - 12mm	1



Standard of Compliance
IEC60998-2-1:2004
IEC62444:2013
IEC60529:1991+A1:2000
+A2:2013

Specifications
• IP68 (3 bar)

5 Pole Straight

List No.	Terminal	Amps Max	Cable O/D Min-Max	Pack Qty
JOW5	5 pole straight	24A	5 - 12mm	1



Standard of Compliance
IEC60998-2-1:2004
IEC62444:2013
IEC60529:1991+A1:2000
+A2:2013

Specifications
• IP68 (3 bar)

3 Pole Heavy Duty

List No.	Terminal	Amps Max	Cable O/D Min-Max	Pack Qty
JOW3HD	3 pole heavy duty	24A	5 - 12mm	1



Standard of Compliance
IEC60998-2-1:2004
IEC62444:2013
IEC60529:1991+A1:2000
+A2:2013

Specifications
• IP68 (3 bar)

3 Pole Fast Fit

List No.	Terminal	Amps Max	Cable O/D Min-Max	Pack Qty
JOW3PIN	3 pole pin & socket, fast fit	16A	5 - 10mm	1

WATERPROOF; WATERTIGHT

A comprehensive range of Waterproof Connectors



- CE Approved
- Operating Temperature: **-35 to 105°C**
- Barometric Pressure: **86 to 106KPa**
- Plastic Housing: **PA66, V-O, 960°C, PTI:250**
- Metal Parts: **Cu, silver plated**