



Street Lighting Service Cut-outs



Standard of Compliance
BS 7654 IEC 947:1

Specifications

- Fuses not included
- Single LST fuse 25A max
- 16mm² max conductor

Note

- Not suitable for SWA

MC040 SLF Type 1 SNE Cut-Out

List No.	Description	Pack Qty
17710E	SP. fuseway, separate neutral & earth	1



Standard of Compliance
BS 7654 IEC 947:1

Specifications

- Fuses not included
- Single LST fuse 25A max
- 16mm² max conductor

MC040 DN Type Compact Cut-Out

List No.	Description	Pack Qty
12013	Very compact. DP single fuse. 2 grommet entries	1



Standard of Compliance

BS 7654:1997
IEC/EN 60947-1

Specifications

- Fuses not included
- Single LST fuse 25A max
- 25mm² max conductor
- Thermoplastic moulding
- IP43 rated

Titan Type Cut-Out

List No.	Description	Column Type/Wiring	Pack Qty
T020G26	SP single phase, single fuse with earth block and brass plate. 2 x 25mm tubes	Single / Loop-in/out	1
T02AG61	SP single phase, single fuse with earth block and brass plate. 3 x 22mm tubes	Single / Loop-in/out	1
T060G26	DP single phase, single fuse with earth block and brass plate. 2 x 25mm tubes	Single / Loop-in/out	1
T06AG61	DP single phase, single fuse with earth block and brass plate. 3 x 22mm tubes	Single / Loop-in/out	1
T060G12	DP single phase, single fuse with earth block and brass plate. 2 x 20mm grommets	Single / Loop-in/out	1
T080G25	DP single phase, double fuse with earth block and brass plate. 2 x 20mm tubes	Twin / Loop-in/out	1
T2LEXT	Large 2 way extension trough. Suitable for Titan cut outs and Trojan Midi isolator. 120mm x 83mm x 63mm		1

Photocell



Standard of Compliance

BS EN 61347
BS EN 61000
BS EN 55015:2013
BS EN 61547:2009

Specifications

- 20:20 lux unity luminance ratio
- IP66
- Dimmable & programmable
- Tool-free (push & twist) installation
- DALI & Xitanium SR compatible
- Low energy consumption
- 15 year life expectancy with zero maintenance requirements
- Compatible with new LED designs

Zhaga LED Photocell

List No.	Description	Pack Qty
TSLED	49mm diameter x 21mm. Maximum load 400W. Accurate low level luminance switching. Compatible with new LED designs	1

Street Lighting Service Isolator



Standard of Compliance

EC/EN 60269-1
IEC/EN 60947-3

Specifications

- 32A Double Pole switched
- Fuses not included
- Single MD/LD fuse 25A max
- Safety interlock device
- 10mm² max conductor

Certified



Trojan Type Isolator

List No.	Description	Type	Pack Qty
TR2MID	Fuse holder + earth block. 2 x 20mm grommet entry & 6mm ² x 350mm fitted tails. IP44	Midi 2 way	1
TR2MBI	Fuse holder + earth block. 1 x 20mm grommet entry. IP33	Mini 2 way	1