

## PANEL COMPONENTS

# PLASTIC SELECTOR SWITCH FOR PUSH-BUTTON STATION PSA-2SS

**Selector switch head only with metal bezel. Standard  
22.5mm hole fixing.**

### General Characteristics

|                                  |                     |
|----------------------------------|---------------------|
| Standard                         | EN 60947-5-1        |
| Operation                        | 2 position stay put |
| Rated Voltage                    | 380V                |
| Rated Current                    | 10A                 |
| Maximum number of contact blocks | 2                   |
| Tightening Torque                | 0.5 Nm              |
| Diameter of bezel                | 29mm                |
| Depth of bezel with actuator     | 27mm                |
| Back of panel depth              | 43mm                |
| Maximum thickness for fixing     | 7mm                 |
| Operating temperature            | -40 to +70°C        |
| Ingress protection               | IP65                |
| Weight                           | 0.04Kg              |

### Available Accessories

|          |                                   |
|----------|-----------------------------------|
| PPS1     | 1 gang plastic pushbutton station |
| PPS2     | 2 gang plastic pushbutton station |
| PPS3     | 3 gang plastic pushbutton station |
| PA-CB1NC | Contact block 1N/O                |
| PA-CB1NO | Contact block 1N/C                |

### Additional Information

This product is for use by skilled persons or instructed persons. The installation of this product must comply with current IEE regulations. Terminals, including those factory fitted, must be checked for correct tightness before commissioning. All terminals should be periodically checked for correct tightness. The data herein serves only to describe the product and should not be regarded as representing guaranteed properties in the legal sense. We reserve the rights of modification, whilst every care has been taken in ensuring the accuracy of this catalogue, the Supplier accepts no liability whatsoever for any eventuality arising from errors or omissions within its catalogues, brochures or within any online presence.