



## Push-fit



**Standard of Compliance**  
BS 60998-1 60998-2-2




**Specifications**

- 24A / 450V
- 0.5 - 2.5mm<sup>2</sup> solid cable
- 1.5 - 2.5mm<sup>2</sup> stranded cable
- Not suitable for fine stranded cable
- Interlocking stacking design

**Certified**



### SDK Type - T90

List No.	Conductors	Conductor Entry	Pack Qty
SDK3 	3	3 x solid or stranded	100
SDK5 	5	5 x solid or stranded	50
SDK8 	8	8 x solid or stranded	30



**Standard of Compliance**  
BS 60998-1 60998-2-2






**Specifications**


- 24A / 450V
- 0.5 - 2.5mm<sup>2</sup> solid cable

**Certified**



### Miniature Type - T60

List No.	Conductors	Conductor Entry	Pack Qty
MCP2 	2	2 x solid	100
MCP3 	3	3 x solid	50
MCP4 	4	4 x solid	50
MCP5 	5	5 x solid	50
MCP8 	8	8 x solid	50



**Standard of Compliance**  
BS 60998-1 60998-2-2




**Specifications**

- 32A / 450V
- 0.2 - 4mm<sup>2</sup> solid cable
- 0.2 - 4mm<sup>2</sup> stranded cable
- 0.34 - 4mm<sup>2</sup> fine stranded cable

**Certified**



### Lever Type - T85

List No.	Conductors	Conductor Entry	Pack Qty
VPC2 	2	2 x solid, stranded or fine	100
VPC3 	3	3 x solid, stranded or fine	50
VPC5 	5	5 x solid, stranded or fine	25



**Standard of Compliance**  
BS 60998-1 60998-2-2



**Specifications**

- 24A / 450V
- Lighting side
- 0.5 - 2.5mm<sup>2</sup> stranded cable
- 0.5 - 2.5mm<sup>2</sup> solid cable
- 0.5 - 2.5mm<sup>2</sup> fine stranded cable
- Installation side
- 0.75 - 2.5mm<sup>2</sup> solid cable

**Certified**



### Lighting Type - T90

List No.	Conductors	Conductor Entry Lighting Side	Conductor Entry Installation Side	Pack Qty
LPC1 	2	1 x solid, stranded or fine	1 x solid	50
LPC2 	3	1 x solid, stranded or fine	2 x solid	50



**Standard of Compliance**  
IEC 60998-2-3, UL 486C,






**Specifications**

- <20A
- 0.75 - 1.5mm<sup>2</sup> solid, stranded (Red)
- 1.5 - 2.5mm<sup>2</sup> solid, stranded (Blue)
- 2.5 - 4.0mm<sup>2</sup> solid, stranded (Yellow)
- IPX8
- Interlocking stacking design

**Certified**



### Cool Splice Type

List No.	Conductors	Conductor Entry	Pack Qty
NCL1 	2	2 x solid, stranded	1
NCL2 	2	2 x solid, stranded	1
NCL3 	2	2 x solid, stranded	1
NCL4 	2	2 x solid, stranded	1
NCL5 	2	2 x solid, stranded	1



**Standard of Compliance**  
IEC/EN 60998-1, 60998-2-2

**Specifications**

- 41A / 400V
- 2.5 - 6mm<sup>2</sup> stranded cable
- 2.5 - 6mm<sup>2</sup> solid cable
- Not suitable for fine stranded cable

**Certified**



### Big Red Type - T105

List No.	Conductors	Conductor Entry	Pack Qty
BRC3 	3	3 x solid, stranded	25