



Heating Programmers



- Specifications**
- Manual override
 - Timed extension (1-3hrs)
 - Battery reserve
 - Backlight
 - Integrated frost & room stat
 - Universal backplate
 - Surface mounting
 - 24hr/7 day
weekday/weekend options

Certified
CE

Central Heating Programmers

List No.	Description	Pack Qty
DPQE1	LCD, 1 channel, combi suitable	1
DPQE2	LCD, 2 channel, (CH+HW), gravity & pumped	1

Heating Timers



PITWK



GPT247DP



GPT24MF

Certified
CE

General Purpose & Plug-in Timers

List No.	Description	Pack Qty
GPT24MF	Mechanical, immersion heater compatible, 24 hr-15 minute tappets. 16 (6)A 240V. Single back box mounting centres	1
GPT247DP	Digital, 24 hr/7 day-1 minute. 16 (8)A 240V. 6/8 on/off x 7. Panel mounting	1
GPT247DS	Digital 24 hr/7 day-1 minute. 16 (8)A 240V. 6/8 on/off x 7. Surface mounting	1
PIT24M	Mechanical, 24 hr-15 minute tappets. 13A 240V	1
PITWK	Mechanical 7 Day. 13A 240V	1

Room & Cylinder Thermostats



DRT1



TY92A1

Standard of Compliance
IP20
Certified
CE

Room & Cylinder Thermostats

List No.	Description	Pack Qty
WOR101X	10 > 30°C. Analogue. 10 (4)A. Bellows type. SPDT. Heat & cool	1
TY92A1	5 > 35°C. Analogue. 10 (3)A. Bimetallic type. SPST. Heat	1
TY92A3	5 > 35°C. Analogue. 10 (3)A. Bimetallic type. SPDT. Heat & cool	1
TY92A1FST	-5 > 15°C. Analogue. 10 (3)A. Bimetallic type. SPST. Frost	1
DRT1	5 > 35°C. LCD. 5 (3.5)A. Thermistor type. Volts free 24-240V	1
DRT2	5 > 35°C. LCD. 5 (3.5)A Thermistor type. Volts free 24-240V. 5 + 1 + 1 programmable	1
TS5320	10 > 90°C. Analogue. 16 (3)A Cylinder fitting	1



- Specifications**
- Transmitter powered by 2 x AAA Batteries (Not Included)
 - Up to 20M wireless range
 - 868 MHz Frequency
 - DFR1 - Wireless Thermostat
 - DFR2 - Wireless Thermostat with 7 Day timer

Certified
CE

Room Thermostats - RF

List No.	Description	Pack Qty
DFR1	5 > 35°C. LCD. 10 (3)A. Thermistor type. Volts free 24-240V. Transmitter & receiver	1
DFR2	5 > 35°C. LCD. 10 (3)A Thermistor type. Volts free 24-240V. 5 + 1 + 1 programmable	1