NIGLON Control & Automation

ENCLOSED SWITCHGEAR


ENCLOSED MANUAL CHANGEOVER ACCESSORIES 160AUX1/1MC

Bolt on auxiliary contact for 160A manual changeover switch. Allows electrical interlocking, remote indication and alarm monitoring.

General Characteristics

| Ingress protection | IP00 |
|------------------------|--------------|
| Thermal current rating | 10A |
| AC15 rating at 415V | 4A |
| DC13 rating at 220V | 1A |
| Contact arrangement | 1NO and 1NC |
| Terminal Capacity | up to 1.5mm2 |
| Weight | 0.146Kg |

Wiring Diagram



Additional Information

This product is for use by skilled persons or instructed persons. The installation of this product must comply with current IEE regulations. The IP rating of the unit can be compromised if the correct use of glands is not followed. Terminals, including those factory fitted, must be checked for correct tightness before commissioning. All terminals should be periodically checked for correct tightness. The data herein serves only to describe the product and should not be regarded as representing guaranteed properties in the legal sense. We reserve the rights of modificationwhilst every care has been take in ensuring the accuracy of this catalogue, the Supplier accepts no liability whatsoever for any eventuality arising from errors or omissions within its catalogues, brochures or within any online presence.

NiGLON

NC NO