nigLon Control & Automation

ENCLOSED SWITCHGEAR

ENCLOSED MANUAL CHANGEOVER ACCESSORIES 800AUX1/1MC




160A 4 pole manual changeover switch in a glass reinforced polycarbonate enclosure to IP65 IK10. Enclosure has separate lock. The switch handle is padlockable and defeatable.

General Characteristics

ss protection IP00	
nal current rating 10A	
rating at 415V 4A	
rating at 220V 1A	
act arrangement 1NO and 1NC	
inal Capacity up to 1.5mm2	
nt 0.206Kg	
inal Capacity 1NO and 1NC up to 1.5mm2	

Wiring Diagram



Additional Information

This product is for use by skilled persons or instructed persons. The installation of this product must comply with current IEE regulations. The IP rating of the unit can be compromised if the correct use of glands is not followed. Terminals, including those factory fitted, must be checked for correct tightness before commissioning. All terminals should be periodically checked for correct tightness. The data herein serves only to describe the product and should not be regarded as representing guaranteed properties in the legal sense. We reserve the rights of modificationwhilst every care has been take in ensuring the accuracy of this catalogue, the Supplier accepts no liability whatsoever for any eventuality arising from errors or omissions within its catalogues, brochures or within any online presence.

