### **niglon** Control & Automation

# ENCLOSED SWITCHGEAR

## **ENCLOSED MANUAL CHANGEOVER ACCESSORIES** 800AUX2/2MC



160A 4 pole manual changeover switch in a glass reinforced polycarbonate enclosure to IP65 IK10. Enclosure has separate lock. The switch handle is padlockable and defeatable.

#### **General Characteristics**

Ingress protection	IP00
Thermal current rating	10A
AC15 rating at 415V	4A
DC13 rating at 220V	1A
Contact arrangement	2NO and 2NC
Terminal Capacity	up to 1.5mm2
Weight	0.224Kg

#### **Wiring Diagram**

#### **Additional Information**

This product is for use by skilled persons or instructed persons. The installation of this product must comply with current IEE regulations. The IP rating of the unit can be compromised if the correct use of glands is not followed. Terminals, including those factory fitted, must be checked for correct tightness before commissioning. All terminals should be periodically checked for correct tightness. The data herein serves only to describe the product and should not be regarded as representing guaranteed properties in the legal sense. We reserve the rights of modification whilst every care has been take in ensuring the accuracy of this catalogue, the Supplier accepts no liability whatsoever for any eventuality arising from errors or omissions within its catalogues, brochures or within any online presence.

