

GRP ENCLOSURE P403020



Wall mounting polyester enclosure intended for outdoor use. Standard RAL7035 colour. High resistance to harsh weather conditions, corrosion and impact. Easily machinable.


General Characteristics

Standards	IEC 62208, IEC 62262, IEC 60529
Material	Glass fibre reinforced polycarbonate
Flame test	960°C Glow Wire
Ingress Protection	IP66 / IK10
Height	400mm
Width	300mm
Depth	200mm
Useable depth with backplate fitted	138mm
Number of Locks	2
Operating Temperature	-30°C to +105°C
Thermal Class	A
Rated Voltage	1000V
Weight	3.7 Kg

Available Accessories

Document Pocket	A4DOCW
Polyester Backplate 358x260mm	PBP432
Metal Backplate 358x260mm	MBP432
Small Ventilation Device	P-SVD
Large Ventilation Device	P-LVD
Key Lock with Butterfly Handle	P-DL
Padlock Hasp	P-PH
Wall Fixing Kit	P-WFK

Technical Drawing



Additional Information

The data herein serves only to describe the product and should not be regarded as representing guaranteed properties in the legal sense. We reserve the rights of modification, whilst every care has been taken in ensuring the accuracy of this catalogue, the Supplier accepts no liability whatsoever for any eventuality arising from errors or omissions within its catalogues, brochures or within any online presence.