

# niGLON

## Installation Essentials

# Heat Shrink Sleeving Coil



| List No.   |   | Size        | Length |
|------------|---|-------------|--------|
| N-HS48BLK  | ■ | 4.8 - 2.4mm | 10m    |
| N-HS64BLK  | ■ | 6.4 - 3.2mm | 10m    |
| N-HS95BLK  | ■ | 9.5 - 4.7mm | 10m    |
| N-HS127BLK | ■ | 13 - 6.5mm  | 8m     |
| N-HS191BLK | ■ | 19 - 9.5mm  | 5m     |
| N-HS254BLK | ■ | 25 - 13mm   | 3m     |
| N-HS48BLU  | ■ | 4.8 - 2.4mm | 10m    |
| N-HS64BLU  | ■ | 6.4 - 3.2mm | 10m    |
| N-HS95BLU  | ■ | 9.5 - 4.7mm | 10m    |
| N-HS127BLU | ■ | 13 - 6.5mm  | 8m     |
| N-HS191BLU | ■ | 19 - 9.5mm  | 5m     |
| N-HS254BLU | ■ | 25 - 13mm   | 3m     |
| N-HS48BRO  | ■ | 4.8 - 2.4mm | 10m    |
| N-HS64BRO  | ■ | 6.4 - 3.2mm | 10m    |
| N-HS95BRO  | ■ | 9.5 - 4.7mm | 10m    |
| N-HS127BRO | ■ | 13 - 6.5mm  | 8m     |
| N-HS191BRO | ■ | 19 - 9.5mm  | 5m     |
| N-HS254BRO | ■ | 25 - 13mm   | 3m     |
| N-HS48REG  | ■ | 4.8 - 2.4mm | 10m    |
| N-HS64REG  | ■ | 6.4 - 3.2mm | 10m    |
| N-HS95REG  | ■ | 9.5 - 4.7mm | 10m    |
| N-HS127REG | ■ | 13 - 6.5mm  | 8m     |
| N-HS191REG | ■ | 19 - 9.5mm  | 5m     |
| N-HS254REG | ■ | 25 - 13mm   | 3m     |
| N-HS48GRE  | □ | 4.8 - 2.4mm | 10m    |
| N-HS64GRE  | □ | 6.4 - 3.2mm | 10m    |
| N-HS95GRE  | □ | 9.5 - 4.7mm | 10m    |
| N-HS127GRE | □ | 13 - 6.5mm  | 8m     |
| N-HS191GRE | □ | 19 - 9.5mm  | 5m     |
| N-HS254GRE | □ | 25 - 13mm   | 3m     |

### Technical Specifications

|                               |  |
|-------------------------------|--|
| <b>Material</b>               | Halogen free Polyolefin                                |
| <b>Shrink Ratio</b>           | 2:1  |
| <b>Operating Temperature</b>  | -40°c to +135°c  |
| <b>Standard of Compliance</b> | UL224 VW1, AMS-dtl-23053/5 CI 1&2 , CSA 066150, RoHS 2 |
| <b>Extra</b>                  | Flame Retardant , Self Extinguishing                   |

### Technical Drawing

Shrink Ratio - 2:1

