E&OE. Whilst every care has been take in ensuring the accuracy of this catalogue, the Supplie accepts no liability whatsoever for any eventuality arising from errors or omissions within its catalogues, brochures or within any online presence.

60mm

Operational Temperature -5° to +40°C Standards Fuses to BS 1362:1973

sales@niglon.co.uk | www.niglon.co.uk

A contemporary low-profile design, manufactured with stainless steel faceplates, in a luxurious brushed chrome effect finish.

87mm

87mm

 (\bigcirc)

Technical Drawing

 \bigcirc

4.25mm

19.25mm

D-FS13DPFN-BCM **13A Switched Fused**

NiGLON

Wiring Accessories

Connection unit

with Neon & Flex Outlet

Technical Specifications Material Composition: Front Plate Stainless Steel **Rear Housing** Urea Terminals Brass Earth Strap Mild Steel Terminal Screws Steel & Yellow Passivated Silver "on-lay" Copper/Brass Contacts 240V ~ 50Hz Voltage **Current Rating** 13A Terminal Size 5mm Ø **Torque Value** 2.0Nm Cable Size 3x2.5mm² or 2x4.0mm² Back Box Depth 25mm - 47mm Twin Earth Yes **Double Pole** Yes Warranty 20 years **IP Rating** IP20 BS 1363-4-1995+A4-2012

0121 711 1990

NiGLON

USE



