


Miniature Type Push-Fit Connector



Technical Specifications

List No.	MCP2	MCP3	MCP4	MCP5	MCP8
Rating	450V/24A	450V/24A	450V/24A	450V/24A	450V/24A
Temperature	60°C	60°C	60°C	60°C	60°C
Material	Polycarbonate UL94 V2	Polycarbonate UL94 V2	Polycarbonate UL 94 V2	Polycarbonate UL 94 V2	Polycarbonate UL 94 V2
Standard of Compliance	BS 60998-1, 60998-2-2  	BS 60998-1, 60998-2-2  	BS 60998-1, 60998-2-2  	BS 60998-1, 60998-2-2  	BS 60998-1, 60998-2-2  
Conductors	2	3	4	5	8
Conductor Entry	2 x solid	3 x solid	4 x solid	5 x solid	8 x solid
Dimensions	5.5 x 10 x 16 mm (H x W x D)	5.5 x 14 x 16 mm (H x W x D)	5.5 x 18 x 16 mm (H x W x D)	5.5 x 22 x 16 mm (H x W x D)	10 x 18 x 16 mm (H x W x D)
Colour	Grey	Orange	Red	Yellow	Grey



Cable Type : 0.5 - 2.5mm² Solid

Technical Drawing

