



Push-fit



Standard of Compliance
BS 60998-1 60998-2-2

Specifications

- 24A / 450V
- 0.5 - 2.5mm² solid cable
- 1.5 - 2.5mm² stranded cable
- Not suitable for fine stranded cable
- Interlocking stacking design

Certified



SDK Type - T90

List No.	Conductors	Conductor Entry	Pack Qty	
SDK3		3	3 x solid or stranded	100
SDK5		5	5 x solid or stranded	50
SDK8		8	8 x solid or stranded	30



Standard of Compliance
BS 60998-1 60998-2-2

Specifications

- 24A / 450V
- 0.5 - 2.5mm² solid cable

Certified



Miniature Type - T60

List No.	Conductors	Conductor Entry	Pack Qty	
MCP2		2	2 x solid	100
MCP3		3	3 x solid	50
MCP4		4	4 x solid	50
MCP5		5	5 x solid	50
MCP8		8	8 x solid	50



Standard of Compliance
BS 60998-1 60998-2-2

Specifications

- 32A / 450V
- 0.2 - 4mm² solid cable
- 0.2 - 4mm² stranded cable
- 0.34 - 4mm² fine stranded cable

Certified



Lever Type - T85

List No.	Conductors	Conductor Entry	Pack Qty	
VPC2		2	2 x solid, stranded or fine	100
VPC3		3	3 x solid, stranded or fine	50
VPC5		5	5 x solid, stranded or fine	25



Standard of Compliance
BS 60998-1 60998-2-2

Specifications

- 24A / 450V
- Lighting side
- 0.5 - 2.5mm² stranded cable
- 0.5 - 2.5mm² solid cable
- 0.5 - 2.5mm² fine stranded cable
- Installation side
- 0.75 - 2.5mm² solid cable

Certified



Lighting Type - T90

List No.	Conductors	Conductor Entry Lighting Side	Conductor Entry Installation Side	Pack Qty	
LPC1		2	1 x solid, stranded or fine	1 x solid	50
LPC2		3	1 x solid, stranded or fine	2 x solid	50



Standard of Compliance
IEC 60998-2-3, UL 486C,

Specifications

- <20A
- 0.75 - 1.5mm² solid, stranded (Red)
- 1.5 - 2.5mm² solid, stranded (Blue)
- 2.5 - 4.0mm² solid, stranded (Yellow)
- IPX8
- Interlocking stacking design

Certified



Cool Splice Type

List No.	Conductors	Conductor Entry	Pack Qty	
NCL1		2	2 x solid, stranded	1
NCL2		2	2 x solid, stranded	1
NCL3		2	2 x solid, stranded	1
NCL4		2	2 x solid, stranded	1
NCL5		2	2 x solid, stranded	1



Standard of Compliance
IEC/EN 60998-1, 60998-2-2

Specifications

- 41A / 400V
- 2.5 - 6mm² stranded cable
- 2.5 - 6mm² solid cable
- Not suitable for fine stranded cable

Certified



Big Red Type - T105

List No.	Conductors	Conductor Entry	Pack Qty	
BRC3		3	3 x solid, stranded	25