



Lighting Control



TS12K



TS10

- Specification**
- Class 2
 - IP65
 - UV stabilized polycarbonate construction

Photo Electric Switch Cells

List No.	Description	Pack Qty
TS12	3 pin 198-264VAC, 70 Lux switch on. Maximum load 1200W Incandescent, 500W HPS/MH & 250W LED	1
TS12K	3 pin 198-264VAC, 70 Lux switch on. Maximum load 1200W Incandescent, 500W HPS/MH & 250W LED + nema socket, bracket & screws	1
TS12E	3 pin 198-264VAC, 70 Lux switch on with inbuilt VDR surge suppression. Maximum load 1200W Incandescent, 500W HPS/MH & 250W LED	1
TS12EK	3 pin 198-264VAC, 70 Lux switch on with inbuilt VDR surge suppression. Maximum load 1200W Incandescent, 500W HPS/MH & 250W LED + nema socket, bracket & screws	1
TS8	3 pin 198-264VAC, 70 Lux switch on. Maximum load 2400W Incandescent, 1200W HPS/MH & 700W LED (SS8)	1
TS8K	3 pin 198-264VAC, 70 Lux switch on. Maximum load 2400W Incandescent, 1200W HPS/MH & 700W LED + nema socket, bracket & screws (SS8K)	1
TS10	Miniature 16mm solid state pre-wired 198-264VAC 70 Lux on. Maximum load 625W Incandescent, 100W LED	1
TS4M	Miniature 20mm solid state pre-wired 198-264VAC 70 Lux on. Maximum load 1200W Incandescent, 500W HPS/MH & 250W LED	1
TS4MR	Miniature 20mm Remote Sensor version solid state pre-wired 198-264VAC 70 Lux on. Maximum load 1200W Incandescent, 500W HPS/MH & 250W LED	1



- Specification**
- IP20
 - 220-240VAC, 50/60Hz
 - Max load 1200W resistive
 - 300W inductive
 - Installation height 2.2-4m (ceiling type)
 - Detection 6m 360°
 - Time delay 10 seconds to 15 mins
 - Lux level control

Occupancy Detectors

List No.	Description	Pack Qty
NODR360	Recessed, ceiling mounting 65mm ø cut-out, 50mm height	1
NODS120	Surface mounting, 90mm ø cut-out, 28mm height	1



- Specification**
- IP44
 - 10m detection at 180° Scan
 - Time adjustment 5 secs to 7 mins
 - Max load 1000W resistive
 - 10A

Passive Infra-Red (PIR) Detectors

List No.	Description	Pack Qty
PIR500	1000W PIR Detector	1



- Standard of Compliance**
- BS EN 60155:1995
 - IEC60155:1993
 - Certified**

Fluorescent Starter Switches

List No.	Description	Pack Qty
GE22	4-22W 110V or 220/240V	100
GE65	4-65W 220/240V universal	100
GE125	70-125W 220/240V	100



- Standard of Compliance**
- IEC896-2
 - BS6290-4
- Specification**
- Maintenance free
 - ABS (UL94HB) cased.

Sealed Lead-Acid Rechargeable Batteries - 12V

List No.	Size (L x W x H)	Rated Capacity	Pack Qty
VT12012	99 x 43 x 52mm	1.2Ah	1
VT1202	178 x 34 x 60mm	2.0Ah	1
VT1203	134 x 67 x 61mm	3.0Ah	1
VT1207	151 x 65 x 94mm	7.0Ah	1