niglon Control & Automation

ENCLOSED SWITCHGEAR

ROTARY HANDLE KITS // RH-250

Rotary handle for 250A MCCB and CBR breakers. Easier switching using eccentric movement. Only for direct mounting onto MCCB or CBR 250A products. Handle is lockable in the OFF position

General Characteristics	
Standards	BSEN 60947-2
Degree of Ingress	IP40
Construction	ABS plastic
Shaft length	288mm

Shaft cross section	10mm ²
Weight	0.85 Kg
Rated Breaking Capacity @ 415V	35kA
Certification	KEWA S



Additional Information

This product is for use by skilled persons or instructed persons. The installation of this product must comply with current IEE regulations. The IP rating of the unit can be compromised if the correct use of glands is not followed. Terminals, including those factory fitted, must be checked for correct tightness before commissioning. All terminals should be periodically checked for correct tightness. The data herein serves only to describe the product and should not be regarded as representing guaranteed properties in the legal sense. We reserve the rights of modification whilst every care has been take in ensuring the accuracy of this catalogue, the Supplier accepts no liability whatsoever for any eventuality arising from errors or omissions within its catalogues, brochures or within any online presence.

0121 711 1990

sales@niglon.co.uk | www.niglon.co.uk

Niglon