

▶ **24hr / 7 Day - 1 Channel Heating Programmer**



- Specification -
- Manual override • Timed extension (1-3hrs)
 - Battery reserve • Backlight • Integrated frost & room stat
 - Universal backplate • Surface mounting
 - 24hr/7 day weekday/weekend options

List No.	Description	Pack Qty
DPQE1	LCD, combi suitable	1

▶ **24hr / 7 Day - 2 Channel**



- Specification -
- Manual override • Timed extension (1-3hrs)
 - Battery reserve • Backlight • Integrated frost & room stat
 - Universal backplate • Surface mounting
 - 24hr/7 day weekday/weekend options

List No.	Description	Pack Qty
DPQE2	LCD, (CH+HW), gravity & pumped	1

▶ **24hr General Purpose Timer (Mechanical)**



- Specification -
- Mechanical • Immersion heater compatible
 - 24 hr-15 minute tappets • 16 (6)A 240V
 - Single back box mounting centres

List No.	Description	Pack Qty
GPT24MF	Mechanical heating timer	1

▶ **24hr / 7 Day General Purpose Timer (Digital)**



GPT247DP

- Specification -
- Digital • 24 hr/7 day-1 minute
 - 16 (8)A 240V • 6/8 on/off x 7

List No.	Description	Pack Qty
GPT247DP	Panel mounting timer	1
GPT247DS	Surface mounting timer	1



▶ Room Analogue Thermostat



WOR101X

TY92A1

Specification - IP20

WOR101X - 10 > 30°C • Analogue. 10 (4)A • Bellows type • SPDT.
TY92A1 - 5 > 35°C • Analogue. 10 (3)A • Bimetallic type • SPST.
TY92A3 - 5 > 35°C • Analogue. 10 (3)A • Bimetallic type • SPDT.
TY92A1FST - -5 > 15°C • Analogue. 10 (3)A • Bimetallic type • SPST.

List No.	Description	Pack Qty
WOR101X	10 > 30°C - Heat & cool	1
TY92A1	5 > 35°C - Heat	1
TY92A3	5 > 35°C - Heat & cool	1
TY92A1FST	-5 > 15°C - Frost	1

▶ Cylinder Thermostat



Specification -

- IP20
- 10 > 90°C • Analogue. 16 (3)A • Cylinder fitting

List No.	Description	Pack Qty
TSS320	10 > 90°C - Cylinder fitting	1

▶ LCD Room Thermostat



DRT1

Specification -

- IP20
- DRT1 - 5 > 35°C • LCD. 5 (3.5)A • Thermistor type • Volts free 24-240V
- DRT2 - 5 > 35°C • LCD. 5 (3.5)A • Thermistor type • Volts free 24-240V
- 5 + 1 + 1 programmable

List No.	Description	Pack Qty
DRT1	LCD Thermostat	1
DRT2	LCD Thermostat programmable	1

▶ Wireless Room Thermostats



Specification -

- IP20 • Transmitter powered by 2 x AAA Batteries (Not Included)
- Up to 20M wireless range • 868 MHz Frequency

DFR1 - 5 > 35°C • LCD. 10 (3)A • Thermistor type • Volts free 24-240V
 • Transmitter & receiver • Wireless Thermostat

DFR2 - 5 > 35°C • LCD. 10 (3)A • Thermistor type • Volts free 24-240V
 • 5 + 1 + 1 programmable • Wireless Thermostat with 7 Day timer

List No.	Description	Pack Qty
DFR1	LCD Transmitter & receiver	1
DFR2	LCD 5 + 1 + 1 programmable	1