

# niGLON CONTROL & Automation MOTOR CONTROL GEAR STANDARD 4 POLE CONTACTOR AC COIL 4SC100

4 pole contactors are for switching resistive loads, such as lighting or heating. Front or side auxiliary contacts are optional. Din rail mounting.


General Characteristics	
Standards	IEC 60947-4, UL-508
AC-1 Rated Load	100A
AC-3 Rated Power @ 415V	30kW
Rated Operational Voltage (Ue)	≥ 690V
Number of Main Poles	4
Maximum Operation Frequency	1200 per hour
Mechanical Endurance	10 000 000 ops
Electrical Endurance	2 000 000 ops
Width	103mm
Height	124mm
Depth	118mm
Terminal Capacity	10 - 35mm <sup>2</sup>
Tightening Torque	5 Nm
Weight	1.37 Kg
Coil Charactoristics	

## **Technical Drawing**





# Wiring Diagram



\*1 - Optional auxiliary contact unit

**NiGLON** 

#### **Coil Characteristics** Available Coil Voltages 24VAC, 110VAC, 230VAC Inrush Current 220 VA Sealed Current 17 VA Pull-in Voltage 80 - 110 % **Thermal Dissipation** 5 W **Closing time** 16 - 25 ms **Available Accessories** AUX0/2FM Auxilliary Contact 2NC AUX1/1FM Auxilliary Contact 1NO/1NC AUX0/4FM Auxilliary Contact 4NC AUX1/3FM Auxilliary Contact 1NO/3NC AUX2/2FM Auxilliary Contact 2NO/2NC AUX3/1FM Auxilliary Contact 3NO/1NC AUX4/OFM Auxilliary Contact 4NO AUXO/1SM Auxilliary Contact 1NC side mount AUX1/OSM Auxilliary Contact 1NO side mount

# 4PMI135 Mechanical Interlock

## Additional Information

This product is for use by skilled persons or instructed persons. The installation of this product must comply with current IEE regulations. Terminals, including those factory fitted, must be checked for correct tightness before commissioning. All terminals should be periodically checked for correct tightness. The data herein serves only to describe the product and should not be regarded as representing guaranteed properties in the legal sense. We reserve the rights of modification, whilst every care has been take in ensuring the accuracy of this catalogue, the Supplier accepts no liability whatsoever for any eventuality arising from errors or omissions within its catalogues, brochures or within any online presence.

0121 711 1990 sales@niglon.co.uk | www.niglon.co.uk