

Cool Splice Connector



Technical Specifications

Rating	<20A
Ambient temperature	-40 ° C and 75 ° C
Operating temperature	-40 ° C and 105 ° C
Housing Material	Polycarbonate
Contact Material	Tin plated, copper alloy
Standard of Compliance	IEC 60998-2-3, UL 486C
Conductors	2
Conductor Entry	2 x solid, stranded
Certified	CE U KEMA KEUR
Dimensions	21.3 x 12.8x 48mm (HxWxL)
IP Rating	IPX8

Colour Coding

Yellow	12/14 AWG (2.50mm ² / 4.00mm ²)
Blue	14/16 AWG (1.50mm ² / 2.50mm ²)
Red	16/18 AWG (0.75mm ² / 1.50mm ²)

Product Wire Size

List No.	Wire Size	Colours
NCL1	12/14 AWG (2.50mm ² /4.00mm ²)	Yellow
NCL2	16/18 AWG (0.75mm ² /2.50mm ²) & 12/14 AWG (2.50mm ² /4.00mm ²)	Red & Yellow
NCL3	14/16 AWG (1.50mm ² / 2.50mm ²) & 12/14 AWG (2.50mm ² / 4.00mm ²)	Blue & Yellow
NCL4	14/16 AWG (1.50mm ² / 2.50mm ²) & 16/18 AWG (0.75mm ² / 1.50mm ²)	Blue & Red
w	16/18 AWG (0.75mm ² / 1.50mm ²)	Red

Technical Drawing

