nigLon Control & Automation

ENCLOSURES

CONTROL BOXES -CLEAR HIGH LID -JBLL252016C



Multi purpose use junction box RAL7035 colour with transparent lid. High resistance to harsh weather conditions, corrosion and impact. Easily machinable with smooth sides and lid. High profile lid is press fit and secured by 4 screws. Metal backplate available

General Characteristics

Flame test650°C Glow WireIngress ProtectionIP67 / IK10Height250mmWidth200mmDepth160mmOperating Temperature-25°C to +60°CWeight1.49 Kg	Body material	ABS Plastic
Height 250mm Width 200mm Depth 160mm Operating Temperature -25°C to +60°C	Flame test	650°C Glow Wire
Width 200mm Depth 160mm Operating Temperature -25°C to +60°C	Ingress Protection	IP67 / IK10
Depth 160mm Operating Temperature -25°C to +60°C	Height	250mm
Operating Temperature -25°C to +60°C	Width	200mm
, ,	Depth	160mm
Weight 1.49 Kg	Operating Temperature	-25°C to +60°C
	Weight	1.49 Kg
Available Accessories		

711 411 421 6 71 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	
Mounting Plate 228x179mm	MP2217

Additional Information

The data herein serves only to describe the product and should not be regarded as representing guaranteed properties in the legal sense. We reserve the rights of modification, whilst every care has been take in ensuring the accuracy of this catalogue, the Supplier accepts no liability whatsoever for any eventuality arising from errors or omissions within its catalogues, brochures or within any online presence.