

LED LOW PROFILE BEACON LPB110/240-R



Compact LED beacon. Red lens provides homogenous light. Modern, sleek design. Can be combined with a 32 tone sounder. Multiple, selectable light functions include steady, flashing, strobe, pulsating and rotating modes.

General Characteristics

Standard	BSEN 60947-5-1
Input voltage	24 to 48 V AC/DC
Construction	Polycarbonate
Height above panel	68mm
Diameter	110mm
Leakage current	3mA
Ingress protection	IP66
Impact resistance	IK08
Service life	>50,000 h
Operating temperature	-30°C to +60°C
Weight	0.55Kg

Available accessories

ABASE24/48	Audible base 24/48V AC/DC
SBASE	Standard base
WMB-LPB	Wall mount bracket

Additional Information

This product is for use by skilled persons or instructed persons. The installation of this product must comply with current IEE regulations. Terminals, including those factory fitted, must be checked for correct tightness before commissioning. All terminals should be periodically checked for correct tightness. The data herein serves only to describe the product and should not be regarded as representing guaranteed properties in the legal sense. We reserve the rights of modification, whilst every care has been taken in ensuring the accuracy of this catalogue, the Supplier accepts no liability whatsoever for any eventuality arising from errors or omissions within its catalogues, brochures or within any online presence.