

### LED LOW PROFILE BEACON LPB24/48-Y



**Compact LED beacon. Yellow lens provides homogenous light. Modern, sleek design. Can be combined with a 32 tone sounder. Multiple, selectable light functions include steady, flashing, strobe, pulsating and rotating modes.**

#### General Characteristics

|                       |                  |
|-----------------------|------------------|
| Standard              | BSEN 60947-5-1   |
| Input voltage         | 24 to 48 V AC/DC |
| Construction          | Polycarbonate    |
| Height above panel    | 68mm             |
| Diameter              | 110mm            |
| Leakage current       | 3mA              |
| Ingress protection    | IP66             |
| Impact resistance     | IK08             |
| Service life          | >50,000 h        |
| Operating temperature | .-30°C to +60°C  |
| Weight                | 0.55Kg           |

#### Available accessories

|            |                           |
|------------|---------------------------|
| ABASE24/48 | Audible base 24/48V AC/DC |
| SBASE      | Standard base             |
| WMB-LPB    | Wall mount bracket        |

#### Additional Information

This product is for use by skilled persons or instructed persons. The installation of this product must comply with current IEE regulations. Terminals, including those factory fitted, must be checked for correct tightness before commissioning. All terminals should be periodically checked for correct tightness. The data herein serves only to describe the product and should not be regarded as representing guaranteed properties in the legal sense. We reserve the rights of modification, whilst every care has been taken in ensuring the accuracy of this catalogue, the Supplier accepts no liability whatsoever for any eventuality arising from errors or omissions within its catalogues, brochures or within any online presence.