### **NIGLON** Control & Automation

## ENCLOSED SWITCHGEAR

# MILD STEEL ENCLOSED MANUAL CHANGEOVER SWITCH 4 POLE MS400MC



400A 4 pole manual changeover switch in a metal enclosure to IP65. Enclosure has separate lock. The switch handle is padlockable and defeatable. Earth studs are fitted and fixing brackets and earth straps are included

#### **General Characteristics**

Standards	BSEN60947-3
Current Rating at 45°C	400A
Rated Insulation Voltage Ui	1000V
Maximum Operational Voltage Uemax	690V
Dielectric Strength at 50Hz 1min	3.5kV
Rated Impulse Voltage Uimp	12kV
Rated Operational Current AC-22A at 415V	400A
Rated Operational Current AC-23A at 415V	400A
Rated Making Capacity at 415V, 0.35pf AC-23A	4000A
Rated Breaking Capacity at 415V, 0.35pf AC-23A	3200A
Defeatable Handle	Accepts 3 Padlocks
Weight	48.3 Kg
Terminal Width	10mm
Terminal Hole Ø	9mm
Electrical Endurance	1000 ops
Mechanical Endurance	10000 ops


#### **Enclosure Characteristics**


Standards	BSEN61439-1
Overall Dimensions HxWxD	800x600x400mm
Degree of Ingress When Fitted	IP65
Construction	1.2mm Mild Steel
Finish	Epoxy Power Coat
Colour	RAL7035

#### **Available Accessories**


800AUX1/1MC	1NO/1NC Auxilliary Contact
800AUX2/2MC	2NO/2NC Auxilliary Contact
A4DOCW	A4 Document Wallet

#### **Technical Drawing**





#### **Wiring Diagram**



#### Additional Information

This product is for use by skilled persons or instructed persons. The installation of this product must comply with current IEE regulations. The IP rating of the unit can be compromised if the correct use of glands is not followed. Terminals, including those factory fitted, must be checked for correct tightness before commissioning. All terminals should be periodically checked for correct tightness. The data herein serves only to describe the product and should not be regarded as representing guaranteed properties in the legal sense. We reserve the rights of modificationwhilst every care has been take in ensuring the accuracy of this catalogue, the Supplier accepts no liability whatsoever for any eventuality arising from errors or omissions within its catalogues, brochures or within any online presence.