

niglon Control & Automation

ENCLOSURES

PAINTED MILD STEEL ENCLOSURE MS14010030



Wall mounting double door mild steel enclosure painted with epoxy-polyester powder paint. Standard RAL7035 colour. The polyurethane gasket keeps its profile over time to give a high degree of protection against water and dust. Doors open 125° and are reversible. Welded earth studs top and bottom. Fitted, galvanised backplate has return edges for extra rigidity.


General Characteristics

Standards	BSEN 61439-1, BSEN 60529, BSEN 62208, BSEN 62262
Ingress Protection	IP55
Height	1400mm
Width	1000mm
Depth	300mm
Enclosure Steel Thickness	1.2mm
Backplate height	1354mm
Backplate width	954mm
Useable depth with backplate fitted	276mm
Backplate Thickness	2mm
Gland plate dimensions	2 x 416mmx97mm
Number of Locks	3
Operating Temperature	-25°C to +55°C
Operating Relative Humidity at +20°C	90%
Operating Relative Humidity at +40°C	50%
Weight	87 Kg

Available Accessories

Document Pocket	A4DOCW
Spare T Bit Key	STBK
Mild Steel Key Lock	MSKL
Spare Key	SPAK
Wall Mount Brackets (pack of 4)	SSWB
220mm Earth strap	ES22

Technical Drawing



Additional Information

The data herein serves only to describe the product and should not be regarded as representing guaranteed properties in the legal sense. We reserve the rights of modification, whilst every care has been taken in ensuring the accuracy of this catalogue, the Supplier accepts no liability whatsoever for any eventuality arising from errors or omissions within its catalogues, brochures or within any online presence.