

ENCLOSED SWITCHGEAR

REAR OF PANEL ISOLATORS 4 POLE PIS4630



630A 4 pole skeletal switch disconnecter. Complete with shaft and handle. The switch handle is padlockable and defeatable. All terminals are provided with shrouds.

General Characteristics


Standards	BSEN 60947-1 & BSEN 60947-3
Rated Operational Voltage (Ue)	415 V
Rated Operational Frequency	50/60 Hz
Rated Operational Current AC-23	630A
Rated Operational Power (1) AC-23 @ 415V	355kW
Rated Breaking Capacity AC-23 @ 415V	5040A
Rated Conditional Short Current r.m.s. (Icm) / Fuse Cut Off Current (2)	54kA / 630A
Rated Short Time Withstand Current (Icw) @ 690V 1s	20kA
Mechanical Endurance (3)	10000 ops
Electrical Endurance @ 0.65pf	1000 ops
Defeatable Handle	Accepts 3 Padlocks
Weight	7.6 Kg
Terminal Bolt Size	M12 x 40
Terminal Tightening Torque	50...75 Nm
Operating Torque	21Nm

(1) The kW ratings are accurate for three phase 1500 rpm standard asynchronous motors.

(2) In single phase test to IEC629

(3) Divided by 2 for operational cycle

Wiring Diagram



Additional Information

This product is for use by skilled persons or instructed persons. The installation of this product must comply with current IEE regulations. The IP rating of the unit can be compromised if the correct use of glands is not followed. Terminals, including those factory fitted, must be checked for correct tightness before commissioning. All terminals should be periodically checked for correct tightness. The data herein serves only to describe the product and should not be regarded as representing guaranteed properties in the legal sense. We reserve the rights of modification whilst every care has been taken in ensuring the accuracy of this catalogue, the Supplier accepts no liability whatsoever for any eventuality arising from errors or omissions within its catalogues, brochures or within any online presence.